


APPLICATION MADE EASY

Our Security Glazing Tape is manufactured in a range of thicknesses and lengths with the width specified to match the rebate/upstand height. We recommend the minimum contact width to the frame should be 10mm but the greater the width the better the performance. Always ensure a clean and dry surface, using the correct size of tape aligned to the edge of the rebate/upstand without being stretched. Carefully butt, or mitre corners immediately prior to glazing and remove the protective siliconised release paper. Then finally clip the external beads into place.

Security Glazing Tape is recommended to be used under 20% compression in order to maintain pressure on the external bead/glazing gasket.

SPECIFICATION

PVC and PE security glazing tape

Thickness (mm)	1	1.5	2	3	4	5	6	8
Roll length (m)	50	50	40	25	20	15	15	10
Colours	 <ul style="list-style-type: none"> • PVC Standard Black and White. Also available in various other colours. • PE Standard Black and White only. 							
Storage	<ul style="list-style-type: none"> • Store in dry conditions and apply between +10° and +35°c. • Shelf life 1 year. 							

A more detailed specification including physical properties is available if required.

Quotations, Free Tape Samples and Technical assistance are immediately available



**GLAZING
PRODUCTS**



Darlaston Road, Wednesbury, West Midlands WS10 7TN Tel: 0121 526 4048 Fax: 0121 526 4658

